

GE3000HTC

Air Mover



Features
High air volume, low noise
Lightweight design
High efficiency and energy saving
Easy maintenance
Controlador: Manual control

Parameter Information	
Maximum Airflow:	3000 CFM
Sound Pressure:	77 dB
Product Weight:	27.51 lbs
Product Dimensions:	16.06 × 14.02 × 17.24 in
Operating Voltag:	110V-120V,60Hz 224W
Power Cord:	20 ft
Temperature Range:	23-160 °F
Functioning Humidity Range:	≤98%

PRODUCT APPLICATION

GE3000HTC is a high-performance wind turbine designed for use in a variety of applications requiring efficient airflow. Its unique snel-shaped design not only optimizes the airflow path but also improves the overall efficiency and durability of the fan. The GE3000HTC uses an advanced aerodynamic design to deliver a stable and efficient airflow output to meet the needs of a wide range of applications.

The fan is equipped with a pull rod and carpet buckle design, so that users can easily move the fan to the desired position, and stable fixed on the ground, and easy to use on different occasions. This air mover is not only versatile but also extremely flexible. With 3 speed settings 4 operating angles (0°, 90°, +10°, -10°), and a built-in 3-hour timer, it is not only perfect for air drying, but also effectively improves indoor ventilation and air circulation. The specially designed carpet clamp can firmly fix the carpet and achieve fast drying.

The GE3000HTC is equipped with a timer function that allows you to set up to three hours of automatic uptime. This function not only facilitates the use of the user but also helps to save energy and extend the service life of the fan. The fan is made of high-quality materials, with corrosion and wear resistance and other characteristics, and can run stably in harsh environments for a long time. Products comply with relevant safety standards, with overload protection, short circuit protection, and other safety functions to ensure the safety of users during use.

The snail blower GE3000HTC is suitable for various occasions requiring efficient airflow, such as construction sites, warehouses, workshops, basements, etc. Its portability and timing make it an ideal air circulation solution for these situations.



- 18H timer
- 3-Speed adjustable airflow
- Handle Caster Kit
- 20 ft Power Cord
- Carpet Buckle

3000CFM

Stackable





CARRYING HANDLE

CARRYING HAND AND CORD WRAP

20 ft. long power cord

SPEED SWITCH 3 high-velocity speeds ADJUSTABLE TIMER Maximum setting of 3 hours

CARPET BUTTON






















ALORAIR SOLUTIONS INC:

Web: www.alorair.com Add: 14752 Yorba Ct, Chino, CA 91710, US

E-mail: sales@alorair.com Tel: (888) -990-7469

