

Air Mover



Features

- High air volume, low noise
- Lightweight design
- High efficiency and energy saving
- Easy maintenance
- Controlador: automatic control

Parameter Information

Maximum Airflow:	3000 CFM
Sound Pressure:	77 dB
Product Weight:	27.6 lbs
Product Dimensions:	16.06 × 14.02 × 17.24 in
Operating Voltag:	110V-120V,60Hz 224W
Power Cord:	20 ft
Temperature Range:	23-160 °F
Functioning Humidity Range:	≤98%

PRODUCT APPLICATION

The GE3000HCW is an industrial fan that integrates advanced technology and user-friendly design, especially suitable for a variety of applications requiring efficient airflow. Its unique snail shape design is not only beautiful but also optimizes the airflow path, improving the overall performance and durability of the fan. At the same time, the fan is also equipped with a pull rod, timer, and APP control functions, which provides great convenience for users. Advanced aerodynamic design ensures excellent ventilation with low energy consumption.

Suitable for construction sites, warehouses, workshops, and other occasions, to meet the high demand for air circulation. With a pull bar, users can easily move the fan to the desired position. This air mover is not only versatile but also extremely flexible. With 3 speed settings 4 operating angles (0°, 90°, +10°, -10°), and a built-in 3-hour timer, it is not only perfect for air drying, but also effectively improves indoor ventilation and air circulation. The specially designed carpet clamp can firmly fix the carpet and achieve fast drying. Compact design, small space, easy to store and transport. Built-in timer for up to three hours of automatic running time.

The timer function is convenient for users to control the running time of the fan and save energy. Through the smartphone APP, users can remotely control the fan's start, stop, and adjust the wind speed and other functions. The APP interface is simple and clear, the operation is convenient, and the real-time fan status monitoring and fault alarm function are provided.

The fan is made of high-quality materials and exquisite production technology and has the characteristics of corrosion resistance and wear resistance.

In line with relevant safety standards, with overload protection, short circuit protection, and other safety functions, to ensure the safety of users in the process of use.

KEY DESIGN FEATURES

- 3H timer
- 3-Speed adjustable airflow
- Stackable
- 20 ft Power Cord
- Blow at four angles

3000CFM

WHEEL PULLER



CARRYING HANDLE

CARRYING HAND AND CORD WRAP
20 ft. long power cord

DIGITAL PANEL SPEED SWITCH
3 high-velocity speeds
ADJUSTABLE TIMER
Maximum setting of 18 hours

CARPET BUTTON



U.S. Brand
U.S. Company



CARPET CLEAN



FLOOD RESTORATION



HOUSE RENOVATION



COMMERCIAL USE



WORKSHOP



WAREHOUSE

ALORAIR SOLUTIONS INC:

Web: www.alorair.com

E-mail: sales@alorair.com

Add: 14752 Yorba Ct, Chino, CA 91710, US

Tel: (888) -990-7469